

**TRANSFORMER RATED
WATTHOUR METER DATA**
www.uomschool.org

Rs (first gear reduction)

& Design Speed (RPM at TA rating)

MANUFACTURER	TYPE	Rs	Full Load RPM
Landis + Gyr (SIEMENS) (Landis & Gyr) (Duncan)	M-2	100/1	60
	MF, MG	75/1	30
	MH, MR, (transformer rated)	100/1	16 2/3
	ML, MR	100/1	8 1/3
	MT	50/1	8 1/3
	MK, MQ, MS*, (2 1/2 & 15 amp)	100/1	16 2/3
	MK, MQ, (30 amp)	100/1	10
	MK, MQ, (50 amp)	100/1	16 2/3
	MS, (30 amp)	100/1	16 2/3
	MS-E, (30 amp)	100/1	16 2/3
	MX	50/1	8 1/3

*MS transformer rated 2 1/2 only!

GENERAL ELECTRIC	I-16, 20	100/1	33 1/3
	I-30, (15 amp)	100/1	20
	I-30, 50, 55, 60, 70	100/1	16 2/3
	V-2, 3, etc., (3 phase)	100/1	16 2/3
	V-60, etc., (3 phase)	50/1	8 1/3

ITRON (Schlumberger) (Sangamo)	I	50/1	48
	HC	50/1	30
	HF, L 2-3, (3 phase)	100/1	30
	J	100/1	16 2/3
	J-2-3, (15 & 30 amp)	100/1	10
	J-2-3, (50 amp)	100/1	16 2/3
	J-4	50/1	8 1/3
	LC-2-3, (3 phase)	11 1/9 /1	16 2/3
	P2-3, (3 phase)	50/1	8 1/3
	P-20-30	50/1	8 1/3

ELSTER (ABB) (Westinghouse)	OB, CS, (1 & 3 phase)	8 1/3 /1	30
	DS-2-3, (1 phase)	100/1	16 2/3
	DS, (3 phase)	100/1	16 2/3

Revised 2/2006